

Two Sizes - One Great Trailer Design

Both the Cart-Away 1-yard trailer and the 1.75-yard trailer use quality components. All Cart-Away products are assembled with care in the USA. Both use the industry leading GearSaver™ knob for increased gearbox life. Both use the TandemFlex™ fenders to save on dented fenders and are powdercoated to protect the finish of the drum. The 1.75-yds MixKing uses a stronger pintle hitch system than the 2″ ball hitch used on the 1-yard trailer.

Both trailers are a great investment and have the backing of the world's largest producer of trailer based concrete equipment, Cart-Away Concrete Systems, Inc.



Which mixer is right for you? 1yd vs. 1.75yds

7000 GVWR or 1 cubic yard capacity 2" ball

Load range C tires 1820# rating Empty weight 2,440 lbs Tandem 3500 lb. axles 10,000 GVWR or 1.75 cubic yard capacity
Pintel ring
Load range D tires 25/0# rating

Load range D tires 2540# rating Empty weight 2,700 lbs
Tandem 5,200 lb. axles







SPECS

Precision rotating drum

13 hp Motor

Extreme Duty Gearbox

Hydraulic Motor

4 wheel free-backing brakes

Vari-height adjustable tongue

GearSaver Knob for gearbox safety

Hydraulic surge brakes

Dimensions 15'4" L x 5'7" W x 6'10" H

D.O.T. Approved lights

Uni-body hydraulic valve

Tubular A36 structural steel frame

Plastic Tandemflex fenders



OPTIONS

PortaWash

Discharge Chute

Cone Holder

Hour Meter

2-5/16 AutoLock Coupler

2 or 2-5/16 Bulldog Coupler

Tire Upgrade

Electric Brakes

Disc Brakes

Enhanced Visibility

Electric Start

Diesel Engine

Cart-Shield

PortaLoader System

SplashGuard